



SAS 142

Specification

LCD Resolution	128*64
Fingerprint Sensor Resolution	500DPI
Rotational Angle	Total Rotational Angle
FRR	≤0.1%
FAR	≤0.0001%
Identification Time	≤0.1 S
Query Record	Available
Real Time Fingerprint Picture Display	Off-line/On-line
Operating Mode	1:1:1:N
Authentication Mode	Fingerprint/ID Card/Password
Identification Mode	2,000
Fingerprint Capacity	30,000 events
Log Capacity	TCP/IP, RS485
Communication	Available
U disk up/download	Chinese, English, Korean
Language	Available
Voice prompt	Alarm when log capacity is full
Capacity notification	Built-in timing bell
Bell	Normal Open / Normal Closed
Lock Output	wireless remote controlled button
Door Open Button	Can connect the doorbell in every voltages
Doorbell Output	Wiegand 26/34 Optional, Input/ Output Optional
Access Control Interface	Available
Anti-passback	Threatens Alarm, Anti-dismantlement Alarm, Unlock
Alarm	Illegally Alarm, Circumscribed Alarm, Time-out Alarm
Power	DC 12V/1A
Operating environment	Operating Temp: 0~50, Humidity:80%
Size of the Terminal	181(L)*91(W)*36(H)mm